



2016 FOURTRAX RINCON SPECIFICATIONS*

ENGINE	
Engine Type	675cc liquid-cooled OHV semi-dry-sump longitudinally mounted single-cylinder four-stroke
Bore And Stroke	102mm x 82.6mm
Induction	Electronic fuel injection (PGM-FI), 40mm throttle bodies
Ignition	Full-transistorized type with electronic advance
Starter	Electric with auxiliary recoil
DRIVE TRAIN	
Transmission	Automatic with hydraulic torque converter, three forward gears, Reverse, and electronic controls
Driveline	Direct front and rear driveshafts with TraxLok® and torque-sensitive front differential
CHASSIS / SUSPENSION / BRAKES	
Front Suspension	Independent double-wishbone; 6.9 inches travel
Rear Suspension	Independent double-wishbone; 8.0 inches travel
Front Brakes	Dual hydraulic 180mm disc
Rear Brakes	Single hydraulic disc
Front Tires	25 x 8-12
Rear Tires	25 x 10-12
DIMENSIONS	
Length	83.2 inches
Width	46.8 inches
Height	47.5 inches
Wheelbase	50.8 inches
Seat Height	34.5 inches
Ground Clearance	9.1 inches
Curb Weight	657 pounds (Includes all standard equipment, required fluids and a full tank of fuel-ready to ride)
Fuel Capacity	4.4 gallons, including 1.2-gallon reserve
Turning Radius	10.8 feet
OTHER	
Model Id	TRX680FA
Emissions	Meets current California Air Resources Board (CARB) off-road emissions standards.
Available Colors	Red, Olive, Honda Phantom Camo®
Note	No operator under age 16. Honda recommends that all ATV riders take a training course and read their owner's manual thoroughly.
FACTORY WARRANTY INFORMATION	
One Year	Transferable limited warranty; extended coverage available with a Honda Protection Plan.

*All figures are preliminary and subject to change.
 ©2016 American Honda Motor Co., Inc. – Motorcycle Division