

■ Service Data

Tyre size	Front	120/70ZR17M/C (58W)
	Rear	160/60ZR17M/C (69W)
Tyre type	Radial, tubeless	
Recommended Tyres	Front	BRIDGESTONE BT023F G METZELER ROADTEC Z8 INTERACT E
	Rear	BRIDGESTONE BT023R G METZELER ROADTEC Z8 INTERACT
Tyre air pressure	Front	250 kPa (2.50 kgf/cm ² , 36 psi)
	Rear	[Driver only] 250 kPa (2.50 kgf/cm ² , 36 psi) [Driver and passenger] 290 kPa (2.90 kgf/cm ² , 42 psi)
Minimum tread depth	Front	1.5 mm (0.06 in)
	Rear	2.0 mm (0.08 in)
Spark plugs	(standard)	IFR6G-11K (NGK)
Spark plug gap	(non-adjustable)	1.00 to 1.10 mm (0.039 to 0.043 in)
Idle speed	1,200 ± 100 rpm	
Recommended engine oil	Honda 4-stroke motorcycle oil API Service Classification SG or higher, excluding oils marked as "Energy Conserving" or "Resource Conserving," SAE 10W-30, JASO T 903 standard MA	

Engine oil capacity	CTX700A	
	After draining	3.1 litres (3.3 US qt, 2.7 Imp qt)
	After draining & engine oil filter change	3.4 litres (3.6 US qt, 3.0 Imp qt)
Engine oil capacity	CTX700D	
	After draining	3.2 litres (3.4 US qt, 2.8 Imp qt)
	After draining & engine oil filter change	3.4 litres (3.6 US qt, 3.0 Imp qt)
Engine oil capacity	After draining, engine & clutch oil filter change	3.4 litres (3.6 US qt, 3.0 Imp qt)
	After disassembly	4.1 litres (4.3 US qt, 3.6 Imp qt)
	Recommended brake fluid	Honda DOT 4 Brake Fluid
Cooling system capacity	1.69 litres (1.79 US qt, 1.49 Imp qt)	
Recommended coolant	Pro Honda HP Coolant	