

MAINTENANCE SCHEDULE

Perform the Pre-ride Inspection at each scheduled maintenance period.

I : INSPECT AND CLEAN, ADJUST, LUBRICATE OR REPLACE IF NECESSARY

C : CLEAN R : REPLACE A : ADJUST L : LUBRICATE

ITEM	FREQUENCY	WHICHEVER COMES FIRST ↓ →	ODOMETER READING (NOTE (3))							PAGE
			1,000 km (600 mi)	6,000 km (3,750 mi)	12,000 km (7,500 mi)	18,000 km (11,250 mi)	24,000 km (15,000 mi)	30,000 km (18,750 mi)	36,000 km (22,500 mi)	
		EVERY								
* FUEL LINES					I		I		I	
* FUEL FILTER									R	
* THROTTLE OPERATION					I		I		I	130
* CARBURETOR-CHOKE					I		I		I	
* AIR CLEANER		NOTE (1)			R		R		R	126
CRANKCASE BREATHER		NOTE (2)		C	C	C	C	C	C	134
SPARK PLUGS				I	R	I	R	I	R	122
* VALVE CLEARANCE			I	I	I		I		I	
ENGINE OIL		YEAR	R		R		R		R	114
ENGINE OIL FILTER		YEAR	R		R		R		R	116
* CARBURETOR- SYNCHRONIZATION			I		I		I		I	
* CARBURETOR-IDLE SPEED			I	I	I	I	I	I	I	132
RADIATOR COOLANT					I		I		*R	182
* RADIATOR CORE					I		I		I	
* COOLING SYSTEM HOSES & CONNECTIONS					I		I		I	