Specifications

■ Main Components

= man components			
Туре	SC65		
Overall length	87.0 in (2,210 mm)		
Overall width	32.9 in (835 mm)		
Overall height	44.5 in (1,130 mm)		
Wheelbase	58.7 in (1,490 mm)		
Minimum ground clearance	4.92 in (125 mm)		
Caster angle	27° 00′		
Trail	4.5 in (114 mm)		
Curb weight	CB1100 CB1100A	540 lb (245 kg) 549 lb (249 kg)	
Maximum weight capacity*1	351 lb (159 kg)		
Passenger capacity	Rider and 1 passenger		
Minimum turning radius	8.86 ft (2.70 m)		

^{*1} Including rider, passenger, all luggage, and accessories

Displacement	69.5 cu-in (1,140 cm³)		
Bore x stroke	2.89 × 2.65 in (73.5 x 67.2 mm)		
Compression ratio	9.5:1		
Fuel	Unleaded gasoline Recommended fuel octane number: Pump Octane Number (PON) 86 or higher.		
Tank capacity	3.86 US gal (14.6 liters)		
Battery	YTZ14S 12V-11.2Ah (10 HR)		
	1st	3.166	
	2nd	2.062	
Gear ratios	3rd	1.545	
	4th	1.250	
	5th	1.111	
Reduction ratios (primary / final)	1.652 / 2.166		