

Cooling system capacity	2.94 US qt (2.78 L)	
Recommended coolant	Pro Honda HP Coolant	
Recommended drive chain lubricant	Pro Honda HP Chain Lube or equivalent	
Drive chain slack	1.0 - 1.4 in (25 - 35 mm)	
Standard drive chain	RK525ROZ7	
	No. of links	116
Standard sprocket size	Drive sprocket	16T
	Driven sprocket	43T

### ■ Bulbs

Headlight	LED
Brake light/Taillight	LED
Front turn signal light	LED
Rear turn signal light	LED
License plate light	LED

### ■ Fuses

Main fuse	30 A
	<b>CBR1000RR</b> 20 A, 15 A, 10 A
Other fuse	<b>CBR1000RA/S1/S2</b> 30 A, 20 A, 15 A, 10 A

### ■ Torque Specifications

Engine oil drain bolt	22 lbf-ft (30 N·m, 3.1 kgf·m)
Oil filter	19 lbf-ft (26 N·m, 2.7 kgf·m)
Front wheel axle bolt	58 lbf-ft (79 N·m, 8.1 kgf·m)
Front wheel brake caliper mounting bolt	<b>CBR1000RR/RA</b> 33 lbf-ft (45 N·m, 4.6 kgf·m)
	<b>CBR1000S1/S2</b> 30 lbf-ft (40 N·m, 4.1 kgf·m)
Front wheel axle pinch bolt	16 lbf-ft (22 N·m, 2.2 kgf·m)
Rear wheel axle nut	100 lbf-ft (135 N·m, 13.8 kgf·m)