

| Frame (Cont'd)                                  |      |                  |                               |         |
|---|------|------------------|-------------------------------|---------|
| Item  | Q'ty | Thread dia. (mm) | Torque<br>N · m (kg-m, ft-lb) | Remarks |
| <b>Fork:</b>                                    |      |                  |                               |         |
| Fork oil drain bolt                             | 2    | 6                | 8 (0.8, 5.8)                  |         |
| Fork socket bolt                                | 2    | 8                | 20 (2.0, 14)                  |         |
| Fork cap bolt                                   | 2    | 37               | 23 (2.3, 17)                  |         |
| Fork damper rod lock nut                        | 2    | 10               | 20 (2.0, 14)                  |         |
| Secondary master cylinder link rod bracket bolt | 2    | 8                | 27 (2.7, 20)                  | Note 10 |
| <b>Rear Suspension:</b>                         |      |                  |                               |         |
| Swingarm pivot nut                              | 1    | 14               | 108 (10.8, 78)                | Note 9  |
| Drive chain adjuster lock nut                   | 2    | 8                | 22 (2.2, 16)                  |         |
| Rear shock absorber mounting bolt/nut           | 2    | 10               | 42 (4.2, 30)                  | Note 9  |
| Shock link bolt (Frame side)                    | 1    | 10               | 59 (5.9, 43)                  | Note 9  |
| Shock link bolt (Shock arm side)                | 1    | 10               | 42 (4.2, 30)                  | Note 9  |
| Shock arm bolt (Swingarm side)                  | 1    | 10               | 42 (4.2, 30)                  |         |
| <b>Brake System:</b>                            |      |                  |                               |         |
| Front brake master cylinder holder bolt         | 2    | 6                | 12 (1.2, 9)                   |         |
| Front brake master cylinder cap screw           | 2    | 4                | 1.5 (0.15, 1.1)               |         |
| Front brake lever pivot bolt                    | 1    | 6                | 0.8 (0.08, 0.6)               |         |
| Front brake lever pivot nut                     | 1    | 6                | 5.9 (0.59, 4.3)               |         |
| Front brake lever adjuster socket bolt          | 1    | 5                | 3.9 (0.39, 2.9)               |         |
| Front brake switch screw                        | 1    | 4                | 1.2 (0.12, 0.8)               |         |
| Right front brake caliper mounting bolt         | 2    | 8                | 27 (2.7, 20)                  | Note 10 |
| Left front brake caliper lower mounting bolt    | 1    | 8                | 27 (2.7, 20)                  | Note 10 |
| Caliper body B mounting bolt                    | 9    | 8                | 32 (3.2, 23)                  | Note 10 |
| Brake caliper main slide pin                    | 3    | 12               | 27 (2.7, 20)                  |         |
| Brake caliper slide pin                         | 3    | 8                | 23 (2.3, 17)                  |         |
| Pad pin   | 3    | 10               | 23 (2.3, 17)                  |         |
| Caliper bleeder screw                           | 6    | 8                | 5.4 (0.54, 4.0)               |         |
| Secondary master cylinder mounting bolt         | 2    | 6                | 12 (1.2, 9)                   |         |
| Secondary master cylinder push rod joint nut    | 1    | 8                | 18 (1.8, 13)                  |         |
| Secondary master cylinder orifice bolt          | 1    | 8                | 5.4 (0.54, 4.0)               |         |
| Brake link arm bolt/nut                         | 2    | 8                | 27 (2.7, 20)                  | Note 10 |
| Rear master cylinder mounting bolt              | 2    | 6                | 12 (1.2, 9)                   |         |
| Rear master cylinder reservoir                  | 1    | 6                | 12 (1.2, 9)                   |         |
| Rear master cylinder push rod lock nut          | 1    | 8                | 18 (1.8, 13)                  |         |
| Rear master cylinder reservoir joint screw      | 1    | 4                | 1.5 (0.15, 1.1)               |         |
| Brake hose oil bolt                             | 12   | 10               | 35 (3.5, 25)                  |         |
| Brake pipe bolt                                 | 8    | 10               | 17 (1.7, 12)                  | Note 5  |
| Brake hose joint mounting bolt                  | 5    | 6                | 12 (1.2, 9)                   |         |
| Brake hose clamp mounting bolt                  | 6    | 6                | 12 (1.2, 9)                   |         |
| <b>Other Fasteners:</b>                         |      |                  |                               |         |
| Ignition switch torx bolt                       | 2    | 8                | 25 (2.5, 18)                  | Note 10 |