

| Frame (Cont'd) | Item | Q'ty | Thread dia. (mm) | Torque N • m (kg-m, ft-lb) | Remarks |
|-------------------------|---|------|------------------|----------------------------|---------|
| Fork: | | | | | |
| | Fork oil drain bolt | 2 | 6 | 8 (0.8, 5.8) | |
| | Fork socket bolt | 2 | 8 | 20 (2.0, 14) | |
| | Fork cap bolt | 2 | 37 | 23 (2.3, 17) | |
| | Fork damper rod lock nut | 2 | 10 | 20 (2.0, 14) | |
| | Secondary master cylinder link rod bracket bolt | 2 | 8 | 27 (2.7, 20) | Note 10 |
| Rear Suspension: | | | | | |
| | Swingarm pivot nut | 1 | 14 | 108 (10.8, 78) | Note 9 |
| | Drive chain adjuster lock nut | 2 | 8 | 22 (2.2, 16) | |
| | Rear shock absorber mounting bolt/nut | 2 | 10 | 42 (4.2, 30) | Note 9 |
| | Shock link bolt (Frame side) | 1 | 10 | 59 (5.9, 43) | Note 9 |
| | Shock link bolt (Shock arm side) | 1 | 10 | 42 (4.2, 30) | Note 9 |
| | Shock arm bolt (Swingarm side) | 1 | 10 | 42 (4.2, 30) | |
| Brake System: | | | | | |
| | Front brake master cylinder holder bolt | 2 | 6 | 12 (1.2, 9) | |
| | Front brake master cylinder cap screw | 2 | 4 | 1.5 (0.15, 1.1) | |
| | Front brake lever pivot bolt | 1 | 6 | 0.8 (0.08, 0.6) | |
| | Front brake lever pivot nut | 1 | 6 | 5.9 (0.59, 4.3) | |
| | Front brake lever adjuster socket bolt | 1 | 5 | 3.9 (0.39, 2.9) | |
| | Front brake switch screw | 1 | 4 | 1.2 (0.12, 0.8) | |
| | Right front brake caliper mounting bolt | 2 | 8 | 32 (3.2, 23) | Note 10 |
| | Left front brake caliper lower mounting bolt | 1 | 8 | 32 (3.2, 23) | Note 10 |
| | Caliper body B mounting bolt | 9 | 8 | 32 (3.2, 23) | Note 10 |
| | Brake caliper main slide pin | 3 | 12 | 27 (2.7, 20) | |
| | Brake caliper slide pin | 3 | 8 | 23 (2.3, 17) | |
| | Pad pin | 3 | 10 | 23 (2.3, 17) | |
| | Caliper bleeder screw | 6 | 8 | 5.4 (0.54, 4.0) | |
| | Secondary master cylinder mounting bolt | 2 | 6 | 12 (1.2, 9) | |
| | Secondary master cylinder push rod joint nut | 1 | 8 | 18 (1.8, 13) | |
| | Secondary master cylinder orifice bolt | 1 | 8 | 5.4 (0.54, 4.0) | |
| | Brake link arm bolt/nut | 2 | 8 | 27 (2.7, 20) | Note 10 |
| | Rear master cylinder mounting bolt | 2 | 6 | 12 (1.2, 9) | |
| | Rear master cylinder reservoir | 1 | 6 | 12 (1.2, 9) | |
| | Rear master cylinder push rod lock nut | 1 | 8 | 18 (1.8, 13) | |
| | Rear master cylinder reservoir joint screw | 1 | 4 | 1.5 (0.15, 1.1) | |
| | Brake hose oil bolt | 12 | 10 | 35 (3.5, 25) | |
| | Brake pipe bolt | 8 | 10 | 17 (1.7, 12) | Note 5 |
| | Brake hose joint mounting bolt | 5 | 6 | 12 (1.2, 9) | |
| | Brake hose clamp mounting bolt | 6 | 6 | 12 (1.2, 9) | |
| Other Fasteners: | | | | | |
| | Ignition switch torx bolt | 2 | 8 | 25 (2.5, 18) | Note 10 |